

Model: Model S

Vehicle System: 00 - Inspection & Service

Region: All

Tech Note: Model S Annual Service

Tech Notes are internal announcements that help to communicate and track new information about Tesla Service concerns.

Date: _____ Odometer Value: _____
VIN: _____ Service Technician: _____

Fill out the column for the annual check being performed. Blacked-out cells are not required for that year's inspection.

The specified operations repeat after year 5. For example, perform Year 1 operations in year 6, and Year 2 operations in year 7.

Actions: V (visual inspection) F (functional check) T (torque check) E (electronic check) CL (clean/lubricate) R (replace)

Component	Action	Year 1 12,500 mi 20,000 km	Year 2 25,000 mi 40,000 km	Year 3 37,500 mi 60,000 km	Year 4 50,000 mi 80,000 km	Year 5 62,500 mi 100,000 km
Brake Fluid	R		☐		☐	
Coolant	R				☐	
Transmission Fluid	R	Every 12 years / 150,000 mi / 240,000 km				
Panoramic roof, if equipped	F, CL	☐	☐	☐	☐	☐
Wiper blades	R	☐	☐	☐	☐	☐
Windshield washer (top off fluid)	F	☐	☐	☐	☐	☐
Doors, hood, and liftgate	V,F	☐	☐	☐	☐	☐
Seat belts	V,F	☐	☐	☐	☐	☐
RKE/passive entry	F	☐	☐	☐	☐	☐
Replace key fob battery	R	☐	☐	☐	☐	☐
Horn, interior/exterior lighting	V,F	☐	☐	☐	☐	☐
Charge port	V,F	☐	☐	☐	☐	☐
Check for active and historical alerts, repair any issues found, clear alerts	V,F	☐	☐	☐	☐	☐
Cabin air filter	R	☐	☐	☐	☐	☐
A/C desiccant bag	R		☐		☐	
Coolant level	V	☐	☐	☐	☐	☐
Radiator/condenser (clear debris if more than 10% blocked)	V	☐	☐	☐	☐	☐
Tire rotation		Every 5,000 mi / 8,000 km				
Record tread depth, FR (replace if 3/32" / 2 mm or less)	V	Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner
Record tread depth, FL (replace if 3/32" / 2 mm or less)	V	Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner
Record tread depth, RR (replace if 3/32" / 2 mm or less)	V	Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner

Record tread depth, RL (replace if 3/32" / 2 mm or less)	V	Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner
Set tire pressure, FR	V					
Set tire pressure, FL	V					
Set tire pressure, RR	V					
Set tire pressure, RL	V					
Record brake pad thickness, FR (replace if 2 mm or less)	V					
Record brake pad thickness, FL (replace if 2 mm or less)	V					
Record brake pad thickness, RR (replace if 2 mm or less)	V					
Record brake pad thickness, RL (replace if 2 mm or less)	V					
Park brake pads: record thickness	V					
Brake fluid level, pipes, and hoses	V	☐	☐	☐	☐	☐
Battery enclosure	V	☐	☐	☐	☐	☐
Coolant leaks	V	☐	☐	☐	☐	☐
Rear subframe components, drive unit	V	☐	☐	☐	☐	☐
Suspension	V	☐	☐	☐	☐	☐
Suspension bolts	T	☐	☐	☐	☐	☐
Steering gear	T					☐
Secondary hood release latch	CL	☐	☐	☐	☐	☐
Alignment	F	☐	☐	☐	☐	☐
Verify normal vehicle operation	F	☐	☐	☐	☐	☐

SERVICE NOTES:

For feedback on the accuracy of this document, email ServiceBulletinFeedback@teslamotors.com.